

**SA4233(A)-Single-energy**



**Pseudo Color Scanning Image**



**◆ General Specification :**

**Tunnel Size:** 420mm×330mm  
**Conveyor Speed:** 0.22m/s  
**Conveyor height :** 272mm  
**Conveyor Max Load:**60kg  
**X ray Dose per inspection** <0.1.25μSv  
**Wire Resolution:** 38 AWG typical  
**Spatial resolution Level:** dia1.0mm, Vertical: dia1.0mm  
**Penetration:** 6-8mm steel  
**Penetration Resolution:** guarantee 32AWG  
**Film Safety :**Guarantee ASA/ISO1600 Film  
**X-ray Leakage:** <2.0 μSv/h (at a distance of 5cm From external housing)

**◆ Image Process :**

**System function:** Power-on self-test, multi-level user management, image management, TIP management, curve diagnosis, system equipment information, image mirroring, 1-16 times stepless amplification, operator training, accurate positioning of package images, clear channel reminder, device information query, fast switching language, U disk upgrade software, one-button calibration, one-button shutdown, etc.  
**Image Enhancement:** 1-16times enlargement continuity, negative, general enhancement, etc  
**Image Recall:** All preceding images recallable, retrieval.  
**Image Archive:** Up to 10,000 images stored automatically, enable transferring to USB disk, and converting to JPG

**Securina Detection System Co., Limited.**

Tel: +86-755-29025099/Mob: +86-159-1416-2649 E-mail: [sebrina@securinadetection.com](mailto:sebrina@securinadetection.com)

X Ray Screening System, Under Vehicle Scanning System, Explosives and Narcotics Detection,  
Liquid Scanner, Walk Through Metal Detectors, Explosive Disposal Device

◆ **Operating Environment:**

**Operation temperature/Humidity:** 0°C-45°C/10%-95%(non-condensing)  
**Storage Temperature/Humidity:** -20°Cto 60°C/ 5%-95%(non-condensing)  
**Operation Power:** 220VAC(±15%)50±3Hz (Optional: 100VAC,110VAC,120VAC,200VAC)  
**Power Consumption:** 1.0KW (max), 0.5KW(working)  
**Noise:** <65db  
**Dimension Size:**  
**Dimensions (L×W×H) :**1810mm x668mm x890 mm  
**X Ray Scanner N.Weight:** 200Kg  
**Gross.Weight:** 250KG  
**Packing Volume:** 1.52CBM(165\*85\*108cm)

◆ **Control Part Character:**

**Control Board:** IMX6\_mainboard-V030  
**RAM:** 1 G  
**CPU:** Cortex A9  
**Storage space:** 500GB

◆ **X-ray Generator:**

**Anode Voltage:** 80kv  
**Anode power:** 0.5mA  
**Generate angle:** 80 degree upward  
**Brand:** Made in China  
**Generate direct:** from top to bottom  
**Cooling / Duty Cycle:** Oil Cooling /100%

◆ **Other Characters:**

**Detect PCB board:** UK brand Sensortech  
**Extension Rollers:** customize size length in optional  
**Computer system:** LINUX system  
**UPS:** 15mins, 30mins, 60mins etc, optiona

